	Minimum Yard Requirements				
				Maximum	Maximum Lot
District	Front	Rear	Side	Building Height	Coverage
	90' from road				
AGP	centerline *	15'	15'	35'	20%
	90' from road				
AGT	centerline **	15'	15'	35'	20%
	90' from road				
AGT w/second dwelling	centerline **	50'	15'	35'	20%
LAR	25' ***	25'	10'	35'	25%
LAR-w/community waste					
system	25' ***	25'	10'	35'	40%
LAR-Accessory structures		5'	5'	35'	25%
RAR	20' ***	50' ****	10'	35'	25%
RAR-Accessory structures	20' ***	5'	5'	35'	25%
	90' from road				
RR	centerline **	50'	15'	35'	20%
VAD	20' ***	6'	6'	35'	25%
CC	50' ***	25'	10'	35'	25%

 $^{^{\}ast}$ or 60' when abutting any other platted street, road or highway.

AGP=Primary Ag
AGT=Transitional Ag
LAR=Lake Area Residential
RAR=River Area Residential
RR=Rural Residential
VAD=Village Area Development
CC=Commercial Corridor

As of 5-10-16

^{**} or 35' when abutting any other platted street, road or highway.

^{***} On a corner lot, the second front is 15'.

^{****10&#}x27; from the property line if not along the river.